

CLEAN-DECK DECK WASH AND BRIGHTENER

WATER BASED SAFE AND EASY TO USE, BIODEGRADABLE AND DOES NOT CONTAIN BLEACH

Clean dirt, mildew and rust stains, Makes up to 9.45L (2.5 gal).

Excellent for pressure treated, pine, cedar, composite and previously stained wood. Safe around vegetation.

DESCRIPTION

Extremely effective concentrated deck wash for all exterior woods such as pressure treated, pine, cedar and composites. Removes dirt, grime, mildew, water and rust stains and cleans existing coatings that are intact. Use to brighten wood to its' natural color after stripping with STRIP-XL, STRIP-X or restoring with WOOD WASH. NOTE: If bare unstained wood is more than 2 years old, grey and weathered then use WOOD WASH for best results.

TEST SURFACE

Test product on a small inconspicuous area to ensure desired results PRIOR to commencing your project! Product may harm baremetal or painted surfaces.

COVERAGE

27 to 110 m² per 3.78 L (300 to 1200 ft² per gallon)

DIRECTIONS

Surface can be damp or dry, above 10°C (50°F) and not in direct sunlight. Wet the surrounding vegetation with water. The residue when rinsing will not harm your vegetation. USE a garden sprayer or synthetic brush to apply product as follows: For Heavy Cleaning dilute 1:1. Medium Cleaning or as a BRIGHTENER: 3:1. Light Cleaning 5:1. WAIT 10-20 minutes and then scrub with a brush. MIST to ensure that product does not dry on your surface. Over agitation of any wet wood surface may raise the grain of the wood. Use caution as surfaces become slippery when wet. RINSE with water using a garden hose or a pressure washer at low PSI (max 500 PSI).

www.biorestore.ca

Distributed by : Martin & Associates Industries

info@martinassociatesind.ca

514-697-3000

WOOD WASH GREY AND WEATHERED

WATER BASED, SAFE AND EASY TO USE, BIODEGRADABLE AND DOES NOT CONTAIN BLEACH

Remove and restores Grey and weathered wood fibers, Mold, mildew and water stains.

Excellent on all types of woods. Safe around vegetation

DESCRIPTION

Extremely effective on all types of exterior wood (decks, fences, siding) to remove and restore grey weathered wood fibers, mould and water stains. Use our wood stripper STRIP-XL if wood has been previously stained or sealed. An easy way to test if the wood has been previously stained or sealed is to pour water onto the wood. If it beads on the surface and does not soak it, then your wood surface has a stain or sealer.

TEST SURFACE

Test product on a small inconspicuous area to ensure desired results PRIOR to commencing your project! Product may harm bare metal or painted surfaces.

COVERAGE

10 to 20m² per 3.78L (100 à 200 pi² per gallon)

DIRECTIONS

Surface should be dry and above 10°C (50°F) and not in direct sunlight. Wet the surrounding vegetation with water. The residue when rinsing will not harm your vegetation. USE a garden sprayer or synthetic brush to apply product as is (do not dilute). WAIT 5-10 minutes and then brush in the direction of the wood grain with a stiff brush. Over agitation of any wet wood surface may raise the grain of the wood. RINSE with water using a garden hose or a pressure washer at low PSI (max 500 PSI) NOTE: Some wood species may darken in color and require use of our wood BRIGHTENER prior to staining with our HYBRID Natural Stain.

www.biorestore.ca

Distributed by : Martin & Associates Industries

info@martinassociatesind.ca

514-697-3000

WOOD-PREP FOR NEW AND STAINED WOOD

WATER BASED SAFE AND EASY TO USE, BIODEGRADABLE AND DOES NOT CONTAIN BLEACH

Enhances stain penetration, Conditions Wood for an even application.

Remove Mill Glaze, Increase stain adhesion.

DESCRIPTION

Removes mill glaze and opens the wood grain to allow for an even penetration of stain. Excellent for water-based stains as it balances the pH of wood surface prior to coating. Suitable for all stains and paints and allows for immediate coating of new wood. NOTE: If your wood is slightly grey or weathered, we recommend using BIORESTORE WOOD WASH first.

TEST SURFACE

Test product on a small inconspicuous area to ensure desired results PRIOR to commencing your project!

COVERAGE

Up to 44m² (475 pi²)

DIRECTIONS

Surface can be damp or dry. Must be above 10°C (50°F) and not in direct sunlight. Thoroughly dissolve contents in 9.5 litres (2-1/2 gallons) of warm water in a plastic pail (not metal). USE a garden sprayer, synthetic brush or roller to apply solution. WAIT 5-10 minutes and then brush in the direction of the wood grain with a stiff brush. MIST surface to ensure that product does not dry on your wood surface. Over agitation of any wet wood surface may raise the grain. RINSE with water using a garden hose or a pressure washer at low PSI (max 500 PSI).

www.biorestore.ca

Distributed by : Martin & Associates Industries

info@martinassociatesind.ca

514-697-3000